



Summary

Request a quote

Catalog

Low Voltage	6
Wire Size/AWG	26 - 22
Plug	Plug - Straight
Locking system	Push-pull
Jacket cable outside diameter [mm]	5.30 - 6.50 mm
Size	SP
Matching parts	SKN.M06.GLLG
Series	REDEL SP - Inner Push-Pull

Technical details

https://www.lemo.com/int_en/solutions/redel/redel-sp-inner-push-pull/san-m06-gla-6g.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Electrical Configuration

Contact Termination Low voltage	Solder	
Insert configuration value	SP.M06 - 6 Low V.	
Insulator	L: PEEK (UL 94 / V-0/1.5)	
Rated current	8.5 Amps	
Test voltage (kV rms) Contact-contact	1.50	
Contact Type	Solder	
Max. Conductor	1 mm^2 (AWG 18)	
Min. Conductor	0.36 mm^2 (AWG 22)	
Air clearance	1.2 mm	
Creepage distance	1.2 mm	
Bucket Dia.	1.1 mm (0.04in)	
Contact Dia.	1.3 mm (0.0512in)	
Low Voltage	6	
Wire Size/AWG	26 - 22	
Form & Material		
Shell style / Model id	SA - Straight plug, key (N) or keys (P, S and T), with grey cable collet	
Plug	Straight	
Housing material	Proprietary sulfone, gray	
Locking system	Push-pull	
Keying	3 keys (alpha=0, gamma=30, plug: male contacts, receptacle: female contacts)	
Variant	Gray collet nut	
Weight	6.66 g	
Environment		
Technical domain	Medical	
Environmental protection (IP rating)	IP50	
Minimal temperature	-50°C / +170°C	

 $\underline{https://www.lemo.com/int_en/solutions/redel/redel-sp-inner-push-pull/san-m06-gla-6g.html}$

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Cable fixation

Cable termination protection	Standard back nut (no additional protection)	
Fixation type	Cable collet	
Jacket cable outside diameter [mm]	5.30 - 6.50 mm	

Recommended By Lemo

Accessories

Tools	
Crimp tool	DPC.91.701.V

Cables

Cable PartNumber	Material	Colour	Cable image
106220	PVC	Black	
12080	PVC	Grey	
160240	PVC	Black	
260250	PVC	Grey	

https://www.lemo.com/int_en/solutions/redel/redel-sp-inner-push-pull/san-m06-gla-6g.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.