



Summary

Request a quote

Catalog		
Low Voltage	8	
Wire Size/AWG	30 - 22	
Plug	Plug - Straight	
Locking system	Push-pull	
Jacket cable outside diameter [mm]	6.60 - 7.50 mm	
Size	SP	
Matching parts	SRN.M08.GLL.7G	
Series	REDEL SP - Inner Push-Pull	

Technical details

Electrical Configuration

2100ti idai comigaration		
Contact Termination Low voltage	Solder	
R (max)	8.5 mOhm	
Insert configuration value	SP.M08 - 8 Low V.	
Insulator	L: PEEK (UL 94 / V-0/1.5)	
Rated current	5 Amps	
Test voltage (kV rms) Contact-contact	1.50	
Contact Type	Solder	
Max. Solid Conductor	0.36 mm^2 (AWG 23)	
Max. Stranded Conductor	0.36 mm^2 (AWG 22)	
Air clearance	0.78 mm	
Creepage distance	0.78 mm	
Bucket Dia.	0.8 mm (0.032in)	
Contact Dia.	0.9 mm (0.0354in)	
Low Voltage	8	
Wire Size/AWG	30 - 22	
Form & Material		
Shell style / Model id	SA - Straight plug, key (N) or keys (P, S and T), with grey cable collet	
Plug	Straight	
Housing material	Proprietary sulfone, gray	
Locking system	Push-pull	
Keying	3 keys (alpha=0, gamma=30, plug: male contacts, receptacle: female contacts)	
Variant	Gray collet nut	
Weight	46.91 g	
invironment		
Technical domain	Medical	
Environmental protection (IP rating)	IP50	
Minimal temperature	-50°C / +170°C	

Cable fixation

Cable termination protection	Standard back nut (no additional protection)	
Fixation type	Cable collet	
Jacket cable outside diameter [mm]	6.60 - 7.50 mm	

Recommended By Lemo

Accessories

Tools	
Crimp tool	DPC.91.701.V

Cables

Cable PartNumber	Material	Colour	Cable image
108220	PVC	Black	